



GAS CAM 2

Our innovative live gas main camera system provides the highest quality inspection. It is a highly robust camera with LED illumination. The camera and its casing are made from Aerospace grade materials, making them very lightweight.

Memory flex push rod cable technology provides a tougher defence against wear and tear and resists spiralling in the main. Increased fibre bonding improves resistance against snapping, whilst retaining its flexibility and low friction during surveys.

HDD display screen provides “day light” visibility at all times.

Long battery life (up to 100hrs) alleviates need for generators of external power source.

KEY FEATURES

- Recordable or non-recordable CCTV footage
- Live metallic and PE launch systems
- 35mm Camera – 75mm Diameter to 150mm Diameter mains (3” to 6”)
- 50mm Camera – 150mm Diameter to 300mm Diameter mains (6” to 12”)
- All types of pipe materials inspected
- Lengths of up to 100 metres in one direction can be achieved.

Control Unit	Camera (35mm)	Camera (50mm)	Battery Pack	Inspection Rod	Launch Head	Optional Extras
10.4" TFT LCD Panel	Stainless steel body	Aluminium body or Stainless Steel	12v 11Ah Lithium Ion	9mm Diameter push rod	Metallic – Vertical angle launch assembly, compatible for connection on WASK drilling base on metallic mains	Self-levelling
1024x768 Resolution	976x496 pixels @ 50Hz	976x496 Pixels @ 50Hz	12v Li-ion fast charger	Polypropylene outer coating	PE – Live launch systems for low and medium pressure.	Meterage arm
Anti-Reflective, sunlight readable screen	12x White LED illumination	18x White LED illumination	12v Socket ✕	120mtr Length	Compatible for connection on 63mm Radius top tee	Company logo embossed onto unit
110v-240v power input		Self-levelling	USB Sockets			Numerous colours for Pelli case
12v power input			Water resistant case			Recordable option to store up to 1 TB. USB and SD card downloadable

*available with 60ah battery pack only